Daily distribution transport



SOR IBÉRICA S.A.

Avda. de la Llibertat, 49 46600 Alzira (Valencia) Spain

Tel. + (34) 96 245 77 00 Fax + (34) 96 245 77 01/18

marketing@soriberica.com

www.soriberica.com







TECHNICAL SHEET

Rear openning with 2 doors

MODEL SP29


Description	Thickness
Floor	95/110mm
Bulkhead	60/90mm
Rear doors	60/90mm
Sidewall	60/90mm
Roof	90mm
Locks	2/4 st st with handle
Hinges	6 st st

ATP/IR/FRC 3500<GRW < 12000KG (N2)

	()
Dimensions	Internal/External
Length	3000/6500mm
Width	2000/2400mm
Height	1900/2600mm

Standard equipment for the box





Polyester rear frame

Antichock rubber on rear doors

Five lips gummi door seals

Galibo lights according to EC regulations

One recessed light in the roof with switch connected to the truck

Handle on the right side of the rear frame

Reinforcements in the roof and/or sidewalls for hanging meat systems

Floor finished in red colour

Steel subframe primed and painted (finished in any colour)

Two medium horizontal antichock rear bumpers

Rear step

St st door retainers

GRP mudguards with gummi mudflaps



SOR IBÉRICA SA, in its continual efforts to meet the needs of its customers, remarks that each and every one of its products are open to be changed or improved. These modifications may or may not appear on the website or any of the communication tools that the company uses. This will often depend whether the site or any other communication tool has been brought up to date or not. Thereof, it is advisable to confirm the conditions of these before placing an order.

Optionalo equipment

Accessories

TIR finition

Tool box

Working lamp

Paper work carrier

Lames curtain

Tail lift installation

Cooling engine installation

Fixed or sliding bulkhead

Any box colour

Side lights

Aluminum subframe

Security lock

ATP/TMP/Type approval

Ventilation windows

Approved retractable sideguard according to EC regulations

Sidewalls

Aluminum quickstrip

St st quickstrip

St st, aluminum or GRP sidewalls

protection

Load restrait rails

Side door with surface or recessed

locks

Hanging meat support

Floor

Carborundum floor

Aluminum floor partial or

complete

St st floor plate protection

Drain pipes

Wheel bypass

Rear doors

St st rear frame
St st door protection

Roof

LED extra internal lights Hanging meat system (any model) Recessed lames curtain

