

SOR IBÉRICA S.A.

Avda. de la Llibertat, 49 46600 Alzira (Valencia) Spain

Tel. + (34) 96 245 77 00 Fax + (34) 96 245 77 01/18

marketing@soriberica.com

www.soriberica.com





SOR BOX FOR URBAN DISTRIBUTION AND LOGISTICS

TECHNICAL SHEET

Palletized transport

MODEL SP33

Description	Thickness
Floor	125mm
Bulkhead	90mm
Rear doors	90mm
Sidewalls	90mm
Roof	110mm
Locks	4 st st with handle
Hinges	6/8 st st

ATP/IR/FRC 12000<GRW ≤ 26000Kg (N3)

12000 (GRW 3 20000Rg (N3)		
	Dimensions	Internal/External
	Length	4100/10000mm
	Width	2300/2590mm
	Height	2300/3100mm
		(ESP)-3265mm

Box standard equipment

Composition

- > GRP floor (glass fiber reinforced plastic) finished in grey colour
- ➤ High resistance 3mm st st rear frame
- Four horizontal rear bumpers for docks protection
- Five lips gummi protection on doors
- St st door retainers
- 250x60mm aluminun quickstrip surface mounted
- W gummi protection on doors
- GRP external cappings
- > St st subframe
- ➤ One internal light recessed mounted for <6000mm length with switch placed in cabin
- ➤ Two internal lights recessed mounted for length ≥6000mm
- > Thermoplastic mudguards with gummi mudflaps
- > Retractable rear Ladder
- Galibo lights according to EC regulation



SOR IBÉRICA SA, in its continual efforts to meet the needs of its customers, remarks that each and every one of its products are open to be changed or improved. These modifications may or may not appear on the website or any of the communication tools that the company uses. This will often depend whether the site or any other communication tool has been brought up to date or not. Thereof, it is advisable to confirm the conditions of these before placing an order.

Optional equipment

Accessories

TIR finition Working light Tool box or extinguisher Lames curtain Tail lift installation Cooling engine installation Fixed partition wall Sliding bulkhead Multi storage panels Any colour box Side lights Security lock Ventilation window Retractable side guard EC approvals ATP or Type approval

Reinforcements for logistics

Customer lavelling

Sidewalls

Recessed aluminum quickstrip
St st quickstrip
Stainless steel, aluminum or GRP
sidewalls protection
Load restrait rails
Double decks recessed rails
Side door

Rear doors

St st door protections

Floor

Aluminum floor partial or complete st st rear frame prolongation Grooved floor St st floor plate Drain pipes Wheels bypass Recessed or Surface mounted rails Rear channel for waste water

Roof

LED extra internal lights
Reinforcements for sliding
bulkhead
Recessed lames curtain
Rear evaporator installation
Load restrait rails









