



SOR BOX FROZEN GOODS TRANSPORT

SOR IBÉRICA S.A.

Avda. de la Libertat, 49
46600 Alzira (Valencia) Spain

Tel. + (34) 96 245 77 00
Fax + (34) 96 245 77 01/18

marketing@soriberica.com
www.soriberica.com



TECHNICAL SHEET Side door without rear doors

MODEL SP5X

Description	Thickness
Floor	110mm
Bulkhead	110mm
Rear frame	110mm
Sidewall	110mm
Roof	110mm
Locks	1 by door
Hinges	2 st st by door

ATP: **IR/RRC**

GRW ≤ 3500KG (N1)

3500 < GRW ≤ 12000kg (N2-N3)

Dims	Internal	External
Length	2380/5575mm	2600/5800mm
Width	1780/2280mm	2000/2450mm
Height	1700/1975mm	1480/2200mm



Box standard equipment

Composition

Heavy duty GRP (glass fiber reinforced plastic) external cappings including corners

Special gummi seals on side doors

Pressure door retainer on each door

GRP mudguards with gummi mudflaps

Two medium horizontal antichock rear bumpers

Galibo lights according to EC regulations

Steel subframe primed and painted (finished in any colour)

One recessed light in the roof with switch connected to the truck

Side stepper for each door

PVC reinforcements on side doors frames

Electrical sensors in each door frame connected to the fridge

Flat and white colour GRP internal skin to help with the cleaning

Roof reinforcements for euthectical plates

Combinations for side doors:

2+2 side doors

3+3 side doors

4+4 side doors

5+5 side doors

6+6 side doors



SOR IBÉRICA SA, in its continual efforts to meet the needs of its customers, remarks that each and every one of its products are open to be changed or improved. These modifications may or may not appear on the website or any of the communication tools that the company uses. This will often depend whether the site or any other communication tool has been brought up to date or not. Thereof, it is advisable to confirm the conditions of these before placing an order.

Optional equipment

Accessories

- Tool box
- ATP/TMP/Type approval
- Cooling engine installation
- Box painted in any colour
- Side lights
- Spray suppression
- Shelves
- Aluminum subframe
- Retractable side guard according to EC regulations
- Customer levelling

Sidewall

- Aluminum quickstrip
- St st quickstrip
- Security lock (int or ext)
- through bar on side doors

Floor

- Drain pipes

Rearframe

- Third braking light

Roof

- Extra LED light
- Euthectical plates installation

