

SOR IBÉRICA S.A.

Avda. de la Llibertat, 49 46600 Alzira (Valencia) Spain

Tel. + (34) 96 245 77 00 Fax + (34) 96 245 77 01/18

marketing@soriberica.com www.soriberica.com







TECHNICAL SHEET Palletized transport

MODEL SP70

Description	Thickness
Floor	125mm
Bulkhead	90mm
Rear doors	60/90mm
Sidewall	45/60mm
Roof	90mm
Locks	2 st st with handle
Hinges	6 st st

ATP/IR/FRC		
12000 <mma (o3)<="" 24000kg="" td="" ≤=""></mma>		
Dimensions	Internal/External	
Length	5500/12500mm	
Width	2540/2590mm	
Height	2300/2900mm	

Box standard equipment

Composition

- GRP floor (glass fiber reinforced plastic) finished in grey colour
- High resistance 3mm st st rear frame
- Four horizontal rear bumpers for docks protection
- Five lips gummi protection on doors
- St st door retainers
- 250x50mm aluminun quickstrip surface mounted
- W gummi protection on doors
- **GRP** external cappings
- St st subframe

One internal light recessed mounted for <6000mm length with switch placed in cabin

Two internal lights recessed mounted for length ≥6000mm

Thermoplastic mudguards with gummi mudflaps

Retractable rear Ladder

Galibo lights according to EC regulation

SOR IBÉRICA SA, in its continual efforts to meet the needs of its customers, remarks that each and every one of its products are open to be changed or improved. These modifications may or may not appear on the website or any of the communication tools that the company uses. This will often depend whether the site or any other communication tool has been brought up to date or not. Thereof, it is advisable to confirm the conditions of these before placing an order.



Optional equipment

Accessories

TIR finition Working lamp Tool box or extinguisher Paperwork carrier Lames Curtain Tail lift installation Cooling engine installation Fixed partition wall Sliding bulkhead Multi storage panels Any colour box Side lights Security lock Ventilation window Retractable sideguard according to Ec regulations ATP or type approval **Reinforcements for logistics Customer lavelling** Front bulkkhead completely opened if requiered Crossing ramp

Sidewalls

Recessed aluminum quickstrip St st quickstrip Stainless steel, aluminum or GRP sidewalls protection Load restrait rails Double decks recessed rails Side door

Rear doors

St st door protections

Floor

Aluminum floor partial or complete st st rear frame prolongation Grooved floor St st floor plate Drain pipes Wheels bypass Recessed or Surface mounted load restrait rails

Roof

LED extra internal lights Reinforcements for sliding bulkhead Recessed lames curtain Rear evaporator installation Load restrait rails

