



# SOR swap body

Ro-Ro transport

SOR IBÉRICA S.A.

Avda. de la Libertat, 49  
46600 Alzira (Valencia) Spain

Tel. + (34) 96 245 77 00  
Fax + (34) 96 245 77 01/18

[marketing@soriberica.com](mailto:marketing@soriberica.com)

[www.soriberica.com](http://www.soriberica.com)



## TECHNICAL SHEET

15-18 europallets transport capacity

# MODEL SP75/20''

Description	Thickness	Dims	
		External	Internal
Length		7150/7400/7820mm	6900/7220/7640mm
Width		2590mm	2470/2500mm
Height		2300/3100mm	2065/2865mm
Floor	125+140mm structure		
Bulkhead	90mm		
Rear doors	60/90mm		
Sidewalls	45/60mm		
Roof	90mm		
Locks	4 st st with handle		
Hinges	6 st st		

  

Handling elements
4 clamps lodgings
4 sling lodgings
2 fork lifter lodgings

  

Fixing elements
4 lodging corners for platform Twist-locks



## Box standard equipment

### Composition

- GRP floor (glass fiber reinforced Plastic) in grey colour specially reinforced for 8 tons forklifts (tare + load)
- Monoblock front bulkhead with aerodynamic design
- Special high resistance 3mm st st rear frame. The st st rear frame gives to this swap body an exceptional hardness to guarantee the rear doors security and maneuverability
- Four antichock rear bumpers
- Five lips rubber seal on rear doors
- Cylindric antichock rubbers on rear doors
- Heavy duty GRP cappings
- Surface mounted 250x60mm aluminum quickstrip on side walls
- ST-42 steel quality lower structure sandblasted with 60 microns prime and finished with 60 microns colour or galvanized
- Four telescopic 16/18Tm landing legs
- Rear frame fully finished in st st to resist atmospheric agents and the doors to function correctly throughout the life of the vehicle
- Handling and fixing elements mentioned fulfill DIN 70013 and DS2146.3 normative

## Optional equipment

### Accessories

TIR finition  
 Cooling engine installation  
 Fixed partition wall  
 Sliding bulhead  
 Multi storage panels  
 Personalized colour  
 Customer levelling

### Sidewalls

Recessed aluminum quickstrip  
 St st kickstrip  
 St st, aluminum or GRP sidewalls protection  
 Load restraint rails  
 Double deck recessed rails  
 Side door

### Roof

Air Flow channel  
 Aluminum airflow channel  
 Lames curtain  
 Rear evaporator installation recessed or surface mounted  
 Reinforcements for sliding bulkhead  
 Load restraint rails

### Bulkhead

Ventilation window  
 Bulkhead niche for cooling engine

### Rear doors

St st door protections  
 Ventilation windows  
 FAC security lock or any other kind of security locks

### Floor

Aluminun floor partial or complete  
 Stainless steel rear frame prolongation  
 St st plate  
 Load restraint rails recessed or surface mounted  
 Grooved floor system

