



SOR swap body

Ro-Ro transport

SOR IBÉRICA S.A.

Avda. de la Libertat, 49
46600 Alzira (Valencia) Spain

Tel. + (34) 96 245 77 00
Fax + (34) 96 245 77 01/18

marketing@soriberica.com
www.soriberica.com



TECHNICAL SHEET

33 europallets transport capacity

MODEL SP75/40"

Description	Thickness	Dims										
		External	Internal									
Floor	155mm	Length	13600mm / 13355mm									
Bulkhead	105mm	Width	2600mm / 2470/2500mm									
Rear doors	90mm	Height	2600/2900mm / 2400/2700mm									
Sidewalls	45/60mm	<table border="1"> <thead> <tr> <th>Height</th> <th>Example</th> <th>Galibo</th> </tr> </thead> <tbody> <tr> <td>C-351</td> <td>2840</td> <td>2578</td> </tr> <tr> <td>C-354</td> <td>2578</td> <td>2550</td> </tr> </tbody> </table>		Height	Example	Galibo	C-351	2840	2578	C-354	2578	2550
Height	Example	Galibo										
C-351	2840	2578										
C-354	2578	2550										
Roof	90mm	Handling elements 4 clamps lodgings 4 sling lodgings										
Locks	4 st st with handle	Fixing elements 4 lodging corners for platform Twist-locks										
Hinges	8 st st											



Box standard equipment

Composition

- GRP floor (glass fiber reinforced Plastic) in grey colour specially reinforced for 8 tons forklifts (tare + load)
- Monoblock front bulkhead with aerodynamic design
- Special high resistance 3mm st st rear frame. The st st rear frame gives to this swap body an exceptional hardness to guarantee the rear doors security and maneuverability
- Five lips rubber seal on rear doors
- Cylindric antichock rubbers on rear doors
- Grooved GRP circulation channels in bulkhead for better air flow
- Heavy duty GRP cappings
- Surface mounted 250x60mm aluminum quickstrip on side walls
- 3mm thickness st st kickstrip on bulkhead
- 3mm thickness st st guards in upper and bottom sidewalls for handling clamps
- Plate of combined transport
- CSC safety approval plate with Lloyd's Register of Shipping stamp



Optional equipment

Accessories

TIR finition
 Cooling engine installation
 Fixed partition wall
 Sliding bulhead
 Multi storage panels
 Personalized colour
 Customer levelling
 Side lights
 ATP/ Type approvals
 Reinforcements for logistic transport

Sidewalls

Recessed aluminum quickstrip
 St st kickstrip
 St st, aluminum or GRP sidewalls protection
 Load restraint rails
 Double deck recessed rails
 St st cappings

Roof

Air Flow channel
 Aluminum airflow channel
 Lames curtain
 Rear evaporator installation recessed or surface mounted
 Reinforcements for sliding bulkhead
 Load restraint rails
 LED internal lights

bulkhead

ventilation window
 Cooling engine fuel tank

Rear doors

St st door protections
 Ventilation windows
 FAC security lock or any other kind of security locks

Floor

Aluminun floor partial or complete
 Stainless steel rear frame prolongation
 Load restraint rails
 Roller bed system

